

# PRODUCT INFORMATION

## FFP2 NR D respiratory mask by Uvex (121274)



### Scope of Application and Properties

- + **Maximum protection and wearing comfort:** Particle filtering folding mask with valve. The foldable FFP2 respirator offers high protection against particles, aerosols and pollutants with a retaining capacity of more than 94% while maintaining high wearing comfort. In addition, the valve reduces exhalation resistance (even with heavy dust exposure) and minimizes heat and moisture build-up under the mask. This guarantees effective self-protection with high breathability. The comfortable sealing lip in the nose area provides tight seat while wearing the respirator. Moreover, secure fit is assured by the textile headband and flexibly adjustable nose clip. Type-tested in accordance with DIN EN 149:2001+A1:2009 and certified according to the PPE regulation (EU) 2016/425 (personal protective equipment).
- + **Area of application:** Protection from solid and liquid particles, harmful or non-toxic particles and biological agents and also protection from airborne infectious agents (e.g. SARS-CoV-2).
- + **Protection capacity:** Checking the fit of your mask can be easily by carrying out a simple test (the filter material moves when breathing in). Does not protect against gases and vapours! No guarantee for all hazardous substances or chemicals.
- + **Replacement interval:** Depends on inhalation resistance. Maximum use for one shift (8 hours) with at least three breaks in between. Replace immediately in the event of visible contamination.
- + **Before use:** Check for damage! Do not use damaged masks!
- + **Limitation:** Facial hair and scars can impair the fit of the mask and therefore the level of protection.

### Type

Item No.	121274
Version	Unsterile
Size	Universal
Packaging unit (PU)	1 piece

### Material Properties

Latex free	Yes, complete mask
Filter/ mask	Multiple layers of filter material from melt blown polypropylene, polyester
Sealing lip	EVA foam (ethylene-vinyl acetate copolymer)
Valve	ABS (acrylonitrile butadiene styrene copolymer)
Headband	Textile
Nose- and headband clip	Polypropylene
Weight	Excl. Packaging: 14 g

### Filter properties

Retaining capacity	At least 94%
--------------------	--------------

---

<b>Dolomite dust test for FFP2 masks</b>	Passed
<b>Protection against dust, smoke and aerosols in water or oil</b>	Up to 10-fold of threshold
<b>Gases</b>	Unsuitable

---

## CE-Marking

Ce-mark for complex PPE in category III in accordance with PPE Regulation (EU) 2016/425. The type test was based on EN 149:2001+A1:2009. Documented by the EC type test certificate of the manufacturer: Control measures by intermediary notified body BSI Group The Netherlands B.V. (2797).

---

## Notified Body „2797“

BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands.

---

## Quality Management System

Our quality management system is tested and certified by TÜV Product Service GmbH (a certification body accredited by the German Accreditation Council) in accordance with DIN EN ISO 9001:2015. Regular audits and production site inspections guarantee the quality of our products.

---

## Storage and Transport Conditions

- + Dark (protect from direct UV light and sunlight)
- + Cool, dry (Relative humidity 30% - 60%)
- + No contact with pointed and/or sharp objects

---

## Shelf Life

3 years

---

## Manufacturer

Uvex Arbeitsschutz GmbH, Würzburger Str. 181 – 189, 90766 Fürth, [www.uvex-safety.com](http://www.uvex-safety.com)

---

## Distributor

Berner International GmbH, Werner-von-Siemens-Str. 19, 25337 Elmshorn, Tel: +49 4121 43560, Fax: +49 4121 435620  
[info@berner-safety.de](mailto:info@berner-safety.de), [www.berner-safety.de](http://www.berner-safety.de)