

PRODUCT INFORMATION

Respirator Mask FFP-3

Scope and properties

- + **Features:** Half-mask with a high filtering capacity, tight-fitting and leakproof. The soft material and special shape ensure that it can be easily adjusted to fit any face shape. Minimal respiratory resistance and the exhalation valve make it extremely comfortable to wear. The threaded elastic strap makes it easy to put on and take off. Type tested and certified in accordance with EC directive 89/686/EEC (Personal protective equipment).
 - + **Area of application:** Protection from solid and liquid particles, e.g. for handling CMR¹⁾ drugs (e.g. cytostatics, virostatics, biological agents and viruses).
 - + **Protection capacity:** Protection from all CMR drugs or chemicals is not guaranteed. Does not protect against gases and vapours!
 - + **Replacement interval:** Depends on inhalation resistance. Maximum use for one shift (8 hours) with at least three breaks in between. For use with CMR-drugs, a maximum of 4 hrs, so far as there is no obvious contamination. Replace immediately in the event of visible contamination.
 - + **Single use mask – Do not re-use respirator mask!**
 - + **Before use:** Check for damage. Do not use damaged masks.
 - + **Limitation:** Single use mask! Laboratory test results can differ from values obtained in practice considerably and, as a result, the useful life of the mask may increase or decrease. Facial hair and scars can impair the fit of the mask and therefore the level of protection.
 - + **Disposal:** If used in combination with CMR-drugs and contaminated areas/items: waste requiring supervision (waste code: 18 01 04 in accordance with 2000/532/EC); in the event of heavy contamination, waste requiring special supervision (waste code: 18 01 08* in accordance with 2000/532/EC); collect and dispose of waste separately!
- 1): Carcinogenic; mutagenic; toxic to reproduction;

Types

Item no. (non-sterile)	121285
Size	Universal
Packaging unit (PU) (non-sterile)	1 piece
Size of single pouch (PU)	125 mm x 135 mm

Material Properties

Latex free	Yes, complete mask
Design	Several filter material layers
Weight	Excl. packaging : 18 g

Particle Filtration Efficiency

Test aerosol	Minimum filtration efficiency
Sodium chloride	> 99 %
Paraffin oil	> 99 %
Dolomite clogging test (for FFP3-mask) (Dolomite DRB4/15b test aerosol)	Passed
Gases	Unsuitable

CE-Mark

CE-mark for complex PPE in category III in accordance with PPE Regulation (EU) 2016/425. The type test performed was based on EN 149:2001+A1:2009. Documented by the EC type test certificate of the manufacturer. Quality assurance (EC quality assurance system with monitoring): Control measures by intermediary notified body CIOP PIB (1437) in accordance with (EU) 2016/425.

Notified Body „0194“

INSPEC International Ltd (56 Leslie Hough Way, Salford, Gt. Manchester, M6 6AJ, England).

Quality Management System

Our quality management system is tested and certified by TÜV Product Service GmbH (a certification body accredited by the German Accreditation Council) in accordance with DIN EN ISO 9001:2015. Regular audits and production site inspections guarantee the quality of our products.

Storage and Transport Conditions

- Dark (protect from direct UV light and sunlight)
- Cool (-20 to +40°C)
- Dry (Relative humidity 30% - 60%)
- No contact with pointed and/or sharp objects

Shelf Life

3 years

Manufacturer

UVEX Arbeitsschutz GmbH, Würzburger Str. 181 – 189, D- 90766 Fürth

Distributor

Berner International GmbH, Werner-von-Siemens-Str. 19, D-25337 Elmshorn, Tel: +49 4121 43560
info@berner-safety.de, www.berner-safety.de